



When ordering incl. final bore, the drums can be statically balanced upon request

Available materials:
GG
GGG
St 52-3

When ordering advise: diameter $\varnothing d_1$
material
boring $\varnothing d_2$
boring $\varnothing d_3$
boring $\varnothing d_4$
quantity n
x; y

D x B mm	dyn. balancing req. from r.p.m.	$\varnothing d_2$ trial bore mm	$\varnothing d_2$	$\varnothing d_3$	$\varnothing d_4$	n	$\varnothing d_1$	e	f	weight at trial bore kg		inertia kg m ²	
										GG	St	GG	St
$\varnothing 200 \times 75$	2500	20					176	12	12	8,1	8,7	0,04357	0,04792
$\varnothing 250 \times 95$	2000	25					220	15	15	15,5	16,8	0,13183	0,15213
$\varnothing 315 \times 118$	1570	30					285	15	18	26,2	28,5	0,40066	0,44072
$\varnothing 400 \times 150$	1240	35					365	17,5	20	47,9	51,8	1,1311	1,24421
$\varnothing 500 \times 190$	990	50					460	20	22	84,7	91,7	3,2467	3,57137
$\varnothing 630 \times 236$	790	50					580	25	26	160,5	173,8	9,288	10,2168
$\varnothing 710 \times 265$	700	70					650	30	30	241,4	261,4	16,733	18,4063

other dimensions upon request