



- plate thickness: 2 mm
- all covers are provided with handles
- all covers are split as of type TE 400 **)
- all splitted covers provided with lock
- other dimensions upon request (e.g. if R1, R2 larger than max. value)
- possible option hand lever hole (standard shown, left hand operation) *)

| brake type | A | B | F | C | D | E | H | L | M | N | R1/R2 max. | G | K Ø | thread rod |
|------------|-----|-----|-----|-----|-----|-----|------|------|-----|-----|------------|-----|-----|------------|
| TE 160 | 120 | 220 | 190 | 160 | 100 | 8,5 | 420 | 620 | 160 | 460 | 65 | 190 | 140 | bolt Ø16 |
| TE 200 | 155 | 220 | 215 | 140 | 120 | 14 | 540 | 700 | 180 | 520 | 50 | 235 | 140 | M12 x 105 |
| TE 250 | 175 | 220 | 270 | 180 | 150 | 14 | 580 | 830 | 220 | 610 | 70 | 290 | 140 | M12 x 105 |
| TE 315 | 215 | 220 | 317 | 240 | 185 | 14 | 680 | 955 | 270 | 685 | 100 | 330 | 140 | M12 x 105 |
| TE 400 | 260 | 260 | 395 | 320 | 233 | 18 | 790 | 1105 | 320 | 785 | 140 | 395 | 140 | M16 x 105 |
| TE 500 | 320 | 280 | 457 | 400 | 290 | 18 | 880 | 1255 | 395 | 860 | 170 | 420 | 140 | M16 x 105 |
| TE 630 | 400 | 280 | 542 | 510 | 360 | 18 | 1010 | 1395 | 470 | 925 | 225 | 475 | 140 | M16 x 105 |
| TE 710 | 450 | 280 | 595 | 590 | 405 | 18 | 1110 | 1530 | 535 | 995 | 265 | 530 | 140 | M16 x 105 |

When ordering advise: **drum brake type**
dimension R1
dimension R2