



\varnothing 200 \varnothing 250 \varnothing 315 \varnothing 400 \varnothing 500 \varnothing 630 \varnothing 710
 when order brake shoes please advise: drum diameter \varnothing D
 material: aluminium, cast iron, fabricated steel with or without drillings for riveting
 when ordering please advise: drum diameter \varnothing D, friction coefficient $\mu = 0,4$

| $\varnothing d_1$ | B | c | $\varnothing d_2$ | e | f | g ₁ | g ₂ | h | j | k | drillings for riveting | | | | | no. of rivets |
|-------------------|-----|----|-------------------|-----|-----|----------------|----------------|-----|----|-----|------------------------|----------------|----------------|----------------|----------------|---------------|
| | | | | | | | | | | | a ₁ | a ₂ | a ₃ | b ₁ | b ₂ | |
| 200 | 70 | 8 | 20 | 35 | 65 | 32 | 2 | 132 | 15 | 140 | 20 | - | - | 35 | - | 3 |
| 250 | 90 | 8 | 25 | 40 | 80 | 37 | 2 | 162 | 15 | 170 | 20 | - | - | 30 | 45 | 5 |
| 315 | 110 | 10 | 30 | 50 | 100 | 44,5 | 3 | 204 | 18 | 212 | 20 | 75 | - | 33 | 55 | 6 |
| 400 | 140 | 10 | 35 | 62 | 125 | 50 | 3 | 256 | 18 | 260 | 20 | 80 | - | 15 | - | 8 |
| 500 | 180 | 12 | 40 | 80 | 160 | 58 | 3 | 320 | 20 | 320 | 20 | 100 | - | 15 | 90 | 12 |
| 630 | 225 | 12 | 45 | 100 | 200 | 63 | 3 | 400 | 20 | 390 | 20 | 82 | 144 | 20 | 112,5 | 18 |
| 710 | 255 | 15 | 50 | 112 | 224 | 70 | 3 | 452 | 22 | 440 | 20 | 95 | 170 | 20 | 90 | 24 |

other dimensions upon request